


These rugged, electronically actuated machines print the month, day, and year accurately and clearly—even through multiple carbons.\* Attractive enough to place anywhere. The date wheels are set manually. Additional die plates may be ordered to print messages above and/or below the date.

"Quality variations in multicarbon sets and carbonless forms may require factory adjustment of units prior to shipment. Please submit a copy of the forms you will use when placing order.

# AD-E series—automatic stamps

A sensitive trigger switch mechanism activates the electronic circuitry when paper is inserted and the machine will instantaneously register the date. These models are available with engraved brass die plates, plus all these features:

- Adjustable impact (easy potentiometer setting)
- Date wheels lock when printing
- Automatic ribbon advance and reverse
- Sturdy lock to prevent tampering
- Electronic circuitry for long life, dependability, easy maintenance



#### Special model AD-RST-E

Personalized to identify operator

This automatic validating machine was designed for use by bank tellers. Its use has



speeded up bank processing of deposits, and significantly reduced depositors' waiting time. It can

be used whenever more than one person uses the machine and

each user must be identified. Or wherever more than one message is wanted, for example, "SHIPPED," "RECEIVED," "BILLED," etc.


The removable upper die plate can be quickly removed by the user, and the next one inserted by a new user, without opening the case. A dovetail guide positions the incoming plate.

# Specifications:

(the same for all the AD-E series)

Size: H-77/16", W-411/16", D-1013/16"
Weight: 141/2 lbs. (approx.)
Finish: Taupe Hammertone
Power: 115 Volts AC-60 Hz.
Throat depth (edge of paper to top of

date line): 13/16" standard, 19/16" max., 1/8" min. (with extended trigger option.)





#### Service Stamps

**Model SSD service dater** offers unusually large engraving areas surrounding date. Date changes are made by external index knobs. Year must be changed manually. Inked ribbon — rather than ink pad — provides superior impression.

Model SS service stamp is same as SSD, but without date wheels. Unit prints fixed message only.


# Specifications:

Size: H-6", W-4", L-81/4" Weight: 8 lbs. (approx.) Finish: Taupe Hammertone

Throat depth (to top of date): 43/4" (SSD)

#### Ordering information:

Order by model SSD or model SS.





#### **VAD** series

(vertical print automatic date stamps)

VAD-E Series Stamps print anywhere along the left or right margin of a document (prints perpendicular to the inserted edge). Specify left or right when ordering.

### Specifications:

Size: H-7<sup>1</sup>/2", W-10", D-6<sup>3</sup>/4" Weight: 25 lbs. (approx.) Finish: Taupe Hammertone Power: 115 Volts AC-60 Hz.

Throat depth (edge of paper to first character of imprint): approx.: 7/a" standard.

